




WELD PINS: DOUBLE POINTED ARC

To order or specify give:

Product Code: **WP DP** Diameter: Specify Length: Specify **L** Material: Specify



PIN			
SIZE	D*	L	FERRULE CODE
10 GA	.135	AS REQUIRED	F135

*Other diameters available upon request

MATERIAL	LOW CARBON STEEL C - 0.23% max. P - 0.04% max. Mn - 0.90% max. S - 0.05% max.	STAINLESS STEEL AISI grade - 302/304/305 std. Other grades available upon request.
MECHANICAL PROPERTIES	Tensile 60,000 psi (min.) Yield 50,000 psi (min.) Elongation 20% (in 2 inches)	Values for various grades available upon request.
PLATING	Copper coating is standard	Does not apply to Stainless
ANNEALING	Can be annealed if required	Can be annealed if required

WASHERS	Self-Locking washers are available in a variety of sizes, shapes and materials.
----------------	---

APPLICATION	This is the standard weld pin used for insulation fastening when only ARC stud welding equipment is available.
--------------------	--

www.sunbeltstudwelding.com

Sunbelt Stud Welding, Inc.
6381 Windfern Road
Houston, Texas 77040-4915



1-800-462-9353
713-939-8903
fax 713-939-9013