




ALUMINUM FB STUDS



SUNBELT FB aluminum studs, available in diameters from 1/4" to 1/2", have equal weld base and thread diameters.

Typical Use: When minimum fillet dimensions are required at the weld base.

Length Specifications: Available in minimum weld base heights specified, with a maximum of 1-1/4" thread length.

Material: Aluminum alloy 5000 Series; others on request.

Ferrules: All orders include ferrules, which are supplied with the studs and are not sold individually.

To Order: Specify FB studs, quantity, D, L(BW), B, material.

SPECIFICATIONS								
THREAD SIZE	WELD BASE DIA. (NOM)	MINIMUM WELD BASE HEIGHT		MAX THREAD LENGTH	MINIMUM OVERALL LENGTH		APPROXIMATE WELD BEAD DIMENSIONS	
		B-4 WELD	AFTER WELD (NOM)		B-4 WELD	AFTER WELD	DIA.	HGT.
T	D	A(BW)	A(AW)	B	L(BW)	L(AW)	E	F
1/4-20	1/4	5/16	1/8	1-1/4	13/16	5/8	13/32	1/8
5/16-18	5/16	3/8	3/16	1-1/4	1	13/16	15/32	5/32
3/8-16	3/8	13/32	7/32	1-1/4	1-5/32	31/32	5/8	3/16
7/16-14	7/16	15/32	9/32	1-1/4	1-11/32	1-5/32	21/32	7/32
1/2-13	1/2	3/8	3/16	1-1/4	1-1/2	1-5/16	3/4	1/4

www.sunbeltstudwelding.com

Sunbelt Stud Welding, Inc.
 6381 Windfern Road
 Houston, Texas 77040-4915



10-6

1-800-462-9353
 713-939-8903
 fax 713-939-9013