




REFRACTORY STUDS: KNURLED


To order or specify give:
 Product Code: **RA KNRL** Diameter: Specify **D** Length: Specify **L** Material: Specify



STUD			
D	MIN L	KD	FERRULE CODE
5/16	1"	.327	F312

MATERIAL	MILD STEEL C - 0.23% max. P - 0.04% max. Mn - 0.90% max. S - 0.05% max.	STAINLESS STEEL AISI grade - 302/304/305/316 standard Other grades available upon request.
MECHANICAL PROPERTIES	Tensile 60,000 psi (min.) Elongation 20% (in 2 inches)	Values for various grades available upon request.
PLATING	Plating is not standard. Cadmium, Copper, Nickel, and Zinc available upon customer request.	Does not apply to Stainless.

Refractory Anchor: Drive Plate



APPLICATION	Designed to lock on to Sunbelt Stud Welding 5/16" diameter Knurled Studs.
MATERIAL	Mild Steel

Part No.
183-1000-04

DRIVEPLATE: Sold separately. Not a composite part of stud.

www.sunbeltstudwelding.com

Sunbelt Stud Welding, Inc.
 6381 Windfern Road
 Houston, Texas 77040-4915



1-800-462-9353
713-939-8903
 fax **713-939-9013**