




ARC STUDS: FULL BASE

To order or specify give:
 Product Code: **ARC FB** Diameter: Specify **D** Length: Specify **L** Material: Specify



| STUD | | | | | |
|------|-------|--------|--------|--------|--------------|
| D | MIN L | MIN BL | MAX FD | MAX FH | FERRULE CODE |
| 1/4 | 3/4 | .375 | .335 | | F250 |
| 5/16 | 7/8 | .375 | .408 | .125 | F312 |
| 3/8 | | .500 | .488 | .141 | F375 |
| 7/16 | 1-1/8 | .500 | .548 | .158 | F437 |
| 1/2 | 1-1/4 | .500 | .809 | .172 | F500 |
| 5/8 | 1-1/2 | .500 | .765 | .268 | F625 |
| 3/4 | 1-3/4 | .675 | .908 | .335 | F750 |
| 7/8 | 2-1/2 | .750 | 1.048 | .390 | F875 |
| 1 | 2-1/2 | 1.000 | 1.203 | .468 | F1000 |

Standard thread is UNC-2A (Rolled when possible).
 Other threads are available upon request. Maximum standard thread length is 3-7/8".

| | | |
|------------------------------|---|---|
| MATERIAL | MILD STEEL C - 0.23% max. P - 0.04% max. Mn - 0.60% max. S - 0.05% max. | STAINLESS STEEL AISI grade - 302/304/305/316 std. Other grades available upon request. |
| MECHANICAL PROPERTIES | Tensile 60,000 psi (min.) Yield 50,000 psi (min.) Elongation..... 20% (in 2 inches) | Values for various grades available upon request. |
| PLATING | Plating is not standard. Cadmium, Copper, Nickel, and Zinc available upon customer request. | Does not apply to Stainless. |

www.sunbeltstudwelding.com

Sunbelt Stud Welding, Inc.
 6381 Windfern Road
 Houston, Texas 77040-4915



9-5

1-800-462-9353
713-939-8903
 fax **713-939-9013**