




# ARC STUDS: NOTCHED END NAVY

**To order or specify give:**  
 Product Code: **ARC NE**    Diameter: Specify **D**    Length: Specify **L**    Material: Specify



STUD		
D	MIN L	FERRULE CODE
3/16	3/4**	F187

\* Ferrules used with Studs 3/4" long are special "short F" ferrules.

<b>MATERIAL</b>	<b>MILD STEEL</b> C - 0.23% max. Mn - 0.90% max. P - 0.04% max. S - 0.05% max.	<b>STAINLESS STEEL</b> AISI grade - 302/304/305/316 std. Other grades available upon request.
<b>MECHANICAL PROPERTIES</b>	Tensile ..... 60,000 psi (min.) Yield ..... 50,000 psi (min.) Elongation..... 20% (in 2 inches)	Values for various grades available upon request.
<b>PLATING</b>	Plating is not standard. Cadmium, Copper, Nickel, and Zinc available upon customer request.	Does not apply to Stainless.

**Key Hole Slotted Washer (For 3/16 dia. notched end studs)**



**Key Hole Slotted Washer**  
 Part No.  
 033 1000 45 (Galvanized)  
 033 1000 46 (Cadmium Plated)

<b>APPLICATION</b>	Designed to lock on to Navy notched end studs.
<b>MATERIAL</b>	Mild Steel - Cadmium Plated Mild Steel - Galvanized

[www.sunbeltstudwelding.com](http://www.sunbeltstudwelding.com)

**Sunbelt Stud Welding, Inc.**  
 6381 Windfern Road  
 Houston, Texas 77040-4915



**1-800-462-9353**  
**713-939-8903**  
**fax 713-939-9013**