



# Cable Hangers - Crimp Type

## CRIMP TYPE - TECHNICAL DETAILS


| Catalog No. | Cable Diameter in inches From - To |       |
|-------------|------------------------------------|-------|
| JCT 1020    | .305                               | .371  |
| JCT 1040    | .375                               | .531  |
| JCT 1051    | .531                               | .680  |
| JCT 1026    | .437                               | .750  |
| JCT 1027    | .680                               | .900  |
| JCT 1030    | .750                               | 1.000 |
| JCT 1031    | .900                               | 1.224 |




| Catalog No. | Cable Diameter in inches |
|-------------|--------------------------|
| JCT 1181    | .531                     |




| Catalog No. | Cable Diameter in inches From - To |       |
|-------------|------------------------------------|-------|
| JCT 2001    | .305                               | .371  |
| JCT 1052    | .375                               | .531  |
| JCT 1162    | .531                               | .680  |
| JCT 2002    | .437                               | .750  |
| JCT 2003    | .680                               | .900  |
| JCT 2004    | .750                               | 1.000 |
| JCT 2005    | 1.000                              | 1.224 |




| Catalog No. | Cable Diameter in inches |
|-------------|--------------------------|
| JCT 1041    | .500                     |
| JCT 1042    | 1.000                    |
| JCT 1043    | .750                     |
| JCT 1044    | 1.224                    |
| JCT 1045    | .680                     |



| Catalog No. | Cable Diameter in inches From - To |      |
|-------------|------------------------------------|------|
| JCT 1170    | .531                               | .531 |
| JCT 1171    | .325                               | .371 |



Cable Hangers are available in Mild Steel and Stainless Steel types 304 and 316.



### Method of Fastening

1. Weld standard 3/8" dia. stud to overhead deck or bulkhead.
2. Spin desired hanger (crimp, plate or tubular type) onto stud. Secure cable or cables by crimping hanger or banding, depending on type of hanger.

